

# PM-660 AQUA-STOP

## AUXILIARY PRODUCT

**PM-660 AQUA-STOP** is a product specially formulated to seal small leaks in swimming pools. When this viscous liquid is added into the water, it mixes with the water and in contact with air, it solidifies.



### METHOD OF USE AND DOSAGE:

1. Stop the swimming pool pump.
2. Move the filter selector valve to **BY-PASS** or **RECIRCULATE**. **IT IS IMPORTANT THAT THE PRODUCT NOT PASS THROUGH THE FILTER.**
3. Add 1 L/75 m<sup>3</sup> of water to the skimmer.
4. After 40 minutes, run the pump in BY-PASS for at least 8 hours.
5. Note the water level. After 24 hours check if the water level has dropped, using the product again if necessary.
6. Once the product has taken effect, set the filter to its normal position. 24 hours after the addition of the product, you can swim again in the pool.

### PHYSICAL PROPERTIES:

- Appearance: Slightly coloured viscous liquid
- Odour: Odourless
- pH: 12 – 13
- Relative density: 1.50 – 1.55
- Solubility in water: Miscible in water in all proportions

### HAZARDS AND PRECAUTIONARY STATEMENTS:

- Causes skin irritation. Causes serious eye damage.
- Keep out of reach of children.
- Wear protective gloves and eye protection.
- In case of contact with skin: gently wash with plenty of soap and water.
- Call a poison centre or doctor/physician if you feel unwell.

### PACKAGING:

1 L bottles